

SCHEDULE OF QUANTITIES - TIMBER

| NO | SIZE | LENGTH | TIMBER DESCRIPTION | MARK | INSTRUCTIONS | DOLLAR VALUE |
|-----------|---------------|-----------|---|-------|--------------------------------|--------------|
| 1 | 6" x 8" | 7'-0" | 1 1/2" x 6" x 8" FOOTING | F | CUT ON SITE | 3-5 |
| 2 | 6" x 8" | 5'-0" | 6" x 6" x 8" | F | " | 3-5 |
| 3 | 4" x 4" | 6'-2" | 12" x 6" x 4" PILE | P | " | 36-6 |
| 4 | 4" x 4" | 4'-0" | 3" x 6" x 4" | F | " | 6-3 |
| 5 | 4" x 4" | 4'-5" | 3" x 2" x 4" | F | " | 6-0 |
| 6 | 4" x 4" | 5'-5" | 2" x 4" x 4" | F | " | 5-0 |
| 7 | 4" x 3" | 4'-2 1/2" | 1/2" x 4" x 3" | L | FASNET 3" PLAY ONE END | 15-5 |
| 8 | 4" x 3" | 4'-2 1/2" | " | L | FASNET 5" PLAY BOTH ENDS | 15-5 |
| 9 | 4" x 2" | 5'-4" | JOISTS | J | FASNET | 85-5 |
| 10 | 4" x 2" | 2'-5" | " | J | " | 1-8 |
| 11 | 4" x 1" | 5'-8 1/2" | COVER BOARD | C | " | 1-4 |
| 12 | 4" x 1" | 4'-2 1/2" | " | C | " | 5-7 |
| 13 | 4" x 1" | 5'-0" | 4" x 1" x 10" COVER BOARD | CB | CUT ON SITE | 1-8 |
| 14 | 4" x 1" | 5'-0" | 3" x 1" x 5" | CB | " | 1-8 |
| 15 | 4" x 1" | 5'-5" | " | CB | FASNET | 1-6 |
| 16 | 4" x 1" | 5'-4" | " | CB | " | 7-1 |
| 17 | 3" x 2" | 8'-1" | WALL PLATE AT SIDE WALL | W | FASNET | 4-1 |
| 18 | 3" x 2" | 6'-7" | " | W | " | 3-4 |
| 19 | 3" x 2" | 5'-0" | 2 1/2" x 6" WALL PLATE HEAD WALL AND TO PARTITION | W | CUT ON SITE | 2-5 |
| 20 | 3" x 2" | 5'-5" | WALL PLATE TO PARTITION | W | FASNET | 2-3 |
| 21 | 3" x 2" | 5'-4" | " " " " END WALL | W | " | 5-33 |
| 22 | 3" x 2" | 6'-5" | " " " " SIDE WALL | W | " | 6-25 |
| 23 | 3" x 2" | 6'-2" | " " " " " " | W | " | 6-17 |
| 24 | 3" x 2" | 5'-1" | 1/2" x 5" PLATE TO PARTITION | W | CUT ON SITE | 2-6 |
| 25 | 3" x 2" | 5'-1" | 1/2" x 4" " " " " " " | W | " | " |
| 26 | 3" x 2" | 5'-1 1/2" | TOP PLATE AT SIDE | T | FASNET & SCAMP AT END BRG | 8-0 |
| 27 | 3" x 2" | 8'-5" | " " " " " " | T | " | 8-25 |
| 28 | 3" x 2" | 5'-10" | " " " " " " | T | " | 5-5 |
| 29 | 3" x 2" | 5'-10" | " " " " " " | T | " | 5-5 |
| 30 | 3" x 2" | 5'-10" | " " " " " " PARTITION | T | " | 5-2 |
| 31 | 3" x 2" | 5'-4" | " " " " " " " " " " " " | T | " | 7-1 |
| 32 | 3" x 2" | 5'-0" | 2 1/2" x 6" BELOW WINDOW OPENING | B | CUT TO LENGTH ON SITE | 2-9 |
| 33 | 3" x 2" | 5'-2" | LINTEL OVER FIREPLACE | L | FASNET | 2-6 |
| 34 | 3" x 2" | 4'-5" | 1700 | S | " | 32-5 |
| 35 | 3" x 2" | 6'-4" | " AT CUPBOARD | F | " | 4-5 |
| 36 | 3" x 2" | 5'-4" | 2 1/2" x 8" END WALL JACK STUD | J | CUT TO LENGTH ON SITE | 2-7 |
| 37 | 3" x 2" | 7'-0" | FOUR END WALL JACK STUD | J | CUT AND CHECK ON SITE | 3-5 |
| 38 | 4" x 1 1/2" | 7'-0" | WALL BRACING | V | CUT ON SITE & CHECK INTO STEEL | 7-0 |
| 39 | 4" x 1" | 6'-6" | HORIZONTAL CORNER BRACING | H | CUT ON SITE | 3-8 |
| 40 | 3" x 2" | 7'-0" | " " " " " " | H | " " " " " " " " " " | 7-0 |
| 41 | 3" x 2" | 5'-4" | COLLAR TIE | C | TRIM CORNER OFF ON SITE | 16-0 |
| 42 | 3" x 2" | 8'-0" | 3" x 8" COLLAR TIE SUPPORT | C | CUT ON SITE | 6-0 |
| 43 | 3" x 2" | 4'-6" | 3" x 8" COLLAR TIE FELICIT | C | " | 1-1 |
| 44 | 3" x 2" | 5'-4" | 2 1/2" x 8" TIE | C | CUT ON SITE | 10-7 |
| 45 | 3" x 2" | 5'-4" | EDGE BOLLAR | E | FASNET | 7-9 |
| 46 | 3" x 2" | 5'-8" | " | E | " | 1-3 |
| 47 | 3" x 2" | 5'-1" | RASTER | R | FASNET & PRATH BRASS TEMPLAT | 50-0 |
| 48 | 3" x 2" | 7'-6" | 35" x 6" SHEET | S | CUT ON SITE | 16-4 |
| 49 | 3" x 2" | 6'-2" | FASNET BRING FOR LINING | " | FASNET | 6-2 |
| 50 | 2" x 2" | 5'-0" | PULLING | " | CUT ON SITE | 47-0 |
| 51 | 3" x 2" | 7'-0" | FASNET | " | FASNET | 10-5 |
| WEIGHT | | | | | | 182 |
| SUPER FT. | | | | | | 186-1 TOTAL |
| 52 | 8" x 10" x 1" | 7'-7" | T & G FLOORING | FLOOR | FASNET | 83-6 |
| 53 | " " " " | 8'-6" | " | " | " | 53-5 |
| 54 | " " " " | 8'-0" | 6" x 1" x 8" FLOORING TO CUPB | " | CUT ON SITE | 8-0 |
| 55 | " " " " | 5'-0" | T & G FOR CUPB. END PANEL | " | " | 55-0 |
| WEIGHT | | | | | | 182 |
| TOTAL | | | | | | 368-1 TOTAL |

EXTERIOR FRAMING - MATERIALS & QUANTITIES

| | | | | | |
|---|-----------------------|---|--|--|--|
| 10 | 7" x 4" x 8" SHEET | 266 GALV IRON FOR ROOF | | | |
| 11 | 3" x 7" x 10" SHEET | 266 GALV IRON RISING | | | |
| 12 | 1/2" x 6" x 10" SHEET | 266 GALV IRON FOR SIDE WALLS - SEE NOTE SHEET 01 | | | |
| 13 | 1/2" x 6" x 10" SHEET | 266 GALV IRON UNDER FIRE WINDOW | | | |
| 14 | 1/2" x 6" x 10" SHEET | 266 GALV IRON END | | | |
| 15 | 1/2" x 6" x 10" SHEET | 266 GALV IRON ABOVE FIREPLACE | | | |
| 16 | 1/2" x 6" x 10" SHEET | 266 GALV IRON TO ONE SIDE OF FIREPLACE | | | |
| 17 | 1/2" x 6" x 10" SHEET | 266 GALV IRON FOR END WALL AND PARTITION | | | |
| 18 | 1/2" x 6" x 10" SHEET | 266 GALV IRON GABLE - CUT TO SHAPE ON SITE | | | |
| 19 | 1/2" x 6" x 10" SHEET | 266 GALV IRON ABOVE AND BELOW CUPBOARD | | | |
| 20 | 1 ROLL | 1/2" x 6" x 10" GALV IRON SHEET TO GO UNDER IRON | | | |
| 21 | 4" GAL TIE | OF CARBOLATTIC FOR NUTTING IRONS OF FRAMING AND LAMP | | | |
| 22 | 1/2" | PAINTED PAINT FOR OUTSIDE OF FRAMING | | | |
| 23 | 1/2" | TERZOLINE | | | |
| 24 | 5" x 7" | 1/2" GAL TIE FOR CLUSTER FOR FRAMING - CLUSTER FINISH AT 6" CUT | | | |
| 25 | 1 PBT | OF TACK FOR HOLDING IRONS IN PLACE WHILE FINISHING FRAMING | | | |
| WEIGHT 182 | | | | | |
| INSIDE LINING - MATERIALS & QUANTITIES | | | | | |
| INSIDE WALLS TO BE LINED WITH 3/4" THICK PLYWOOD - AS FOLLOWS | | | | | |
| 26 | 6' x 6' x 5' | FOR SIDE AND END WALL CORNER | | | |
| 27 | 6' x 6' x 2' | " | | | |
| 28 | 1' x 6' x 2' | END WALL | | | |
| 29 | 1' x 10' x 2' | BELOW FIRE WINDOW | | | |
| 30 | 1' x 5' x 2' | END | | | |
| 31 | 1' x 5' x 2' | ABOVE FIREPLACE | | | |
| 32 | 1' x 5' x 1' | AT SIDE OF FIREPLACE | | | |
| 33 | 1 ROLL | 1/2" x 6" x 10" GALV IRON SHEET FOR INSULATION - SEE NOTE SHEET 1 | | | |
| 34 | 1 PBT | OF SMALL BRIST FOR FIXING PLYWOOD | | | |
| 35 | 1/2" | 4" GAL TIE OF CLEAR VARNISH FOR PLYWOOD | | | |
| WEIGHT 182 | | | | | |
| MISCELLANEOUS QUANTITIES | | | | | |
| 36 | 7 lbs | 3/4" FLOOR BRIST | | | |
| 37 | 1 lb | OF 2" NAIL | | | |
| 38 | 2 lbs | OF 3" GALV NAILS FOR FOOTING | | | |
| 39 | 16 lbs | OF 4" NAILS FOR FRAMING | | | |
| 40 | 1 ROLL | OF 2" WIDE "DENZO" TAPE | | | |
| 41 | 100 FT. | 8" x 6 GALV WIRE | | | |
| 42 | 10 lbs | OF LEAD HEADED NAIL FOR CORR IRON | | | |
| WEIGHT 182 | | | | | |
| REFERENCE: SEE THE FOLLOWING DRAWINGS FOR FURTHER DETAILS | | | | | |
| P. 210 FIREPLACE | | | | | |
| P. 211 GUY WIRE | | | | | |
| P. 212 WINDOWS & DOORS | | | | | |
| P. 127 BUNKS & TABLE | | | | | |

SPECIFICATION

TIMBER: TIMBER TO BE AS SPECIFIED BELOW OR EQUIVALENT. FLOORING T & G 1" GRADE TREATED EXOTIC TIMBER. SUB FLOOR TIMBER PRESSURE TREATED 50% FLAMING GRADE RADIATA PINE. FRAMING TIMBER NOT FRAMING GRADE RADIATA PINE TREATED 50% FLAMING GRADE RADIATA PINE. ALL TIMBER TO BE WELL SEASONED DRESSED AND GAUGED. PAINTING: INSIDE OF FRAMING AND LEAF TO BE PRIMERED WITH 'CARBOLATTIC'. OUTSIDE OF FRAMING TO BE PRIMED AND PAINTED TERZOLINE. EACH SET WILL BE ALLOCATED A NUMBER. WIRE WILL BE PAINTED ON ONE SIDE OF THE ROOF WITH 'CARBOLATTIC'. THE SQUARE TO BE 4" x 6" WITH 6" WIRE STAKES. INSIDE SURFACE OF IRON TO BE PAINTED 20% BEFORE FINISH TO BRUSH 'TERZOLINE' WELL. IRON TO SAME. PLYWOOD LINING TO HAVE CLEAR VARNISH FINISH. GUY WIRE: TRAPS MAY BE OMITTED WHEN SET UP TO BE BUILT ON A PRELIMINARY SITE.

FRAMING: THE OUTSIDE OF WALL AND ROOF FRAMING TO BE COVERED WITH GALV GRATE 'TERZOLINE' TACKED IN PLACE BEFORE FIXING IRON. PLAT IRON TO BE FIELD WITH GALV CLOUT AT 6" CAP, ALONG ALL LEAF ENDINGS. CORRUGATED IRON TO BE FIXED WITH LEAD HEADED NAIL.

LINING: WALLS TO BE LINED WITH PLYWOOD 3/4" THICK OVER ALUMINIUM FOIL INSULATION. THE INSULATION TO BE SINGLE SIDED AND FIXED WITH THE FOIL PACING THE WALL CAVITY.

1 REFERENCE LIST EXTENDED

2 SCHEDULE CORRECTED RE L-1-70

11-8-60 ENG

2-9-64 AZ

DRAWN RLB

CHECKED RLB

APPROVED RLB

D.P.E HUT 18'8" x 10'8"

SCHEDULE OF QUANTITIES

N.Z. FOREST SERVICE WELLINGTON

FILE NO. 4/10/54

SCALE

DATE 9-1-60

B54

570